



## Batteries



**12 Months Warranty**

|                       |   |                    |
|-----------------------|---|--------------------|
| <b>PART NUMBER</b>    | <b>ED70</b>                                 |                    |
| <b>CHARACTERISTIC</b> | Lead-Acid Battery (Accessible/Maintainable) |                    |
| <b>GROUP SIZE</b>     | N70   |                    |
| <b>CASE AND LID</b>   | Material                                    | Polypropylene (PP) |
|                       | Handle                                      | 1-pc PP handle     |
|                       | Case Colour                                 | black              |
|                       | Lid Colour                                  | black              |
|                       | Ledge / Hold-down                           | NL                 |

### DIMENSIONAL SPECIFICATIONS

| OVERALL DIMENSIONS                       | METRIC (mm) |
|--|-------------|
| LENGTH                                   | 304         |
| WIDTH                                    | 173         |
| HEIGHT (bottom to top cover)             | 203         |
| TOTAL HEIGHT (bottom to top of terminal) | 224         |
| NOMINAL WEIGHT                           | 24.8 kg     |

| TERMINAL DATA        | POSITIVE  | NEGATIVE  |
|----------------------|-----------|-----------|
| TYPE                 | SAE       | SAE       |
| TERMINAL HEIGHT (mm) | 18.5±1.50 | 18.5±1.50 |
| BOTTOM DIAMETER (mm) | 19.5±0.3  | 17.5±0.3  |
| TAPER                | 1:9       | 1:9       |
| POLARITY             |           |           |

### TECHNICAL SPECIFICATIONS

|                          |                     |                                |   |
|--------------------------|---------------------|--------------------------------|---|
| COLD CRANKING AMPS (CCA) | -                   | AMPERE-HOUR (20-HOUR CAPACITY) | 110 AH  |
|                          | Test reference: N/A |                                | Test reference: AS60095.1: 2022               |
| CAPACITY (RC)            | -                   |                                | Rated AH DCH at 10.5 V cut-off                |
|                          | Test reference: N/A | PLATE DESIGN                   | Lead-Calcium Alloy<br>Full Frame Plate Design |
|                          |                     | ELECTROLYTE                    | 36% H2SO4 at 15°C                             |

