



PART NUMBER	SSEFB-B24	
CHARACTERISTIC	Lead-Acid (Enhanced Flooded Battery)	
GROUP SIZE	NS60	
CASE AND LID	Material	Polypropylene (PP)
	Handle	1-pc PP handle
	Case Colour	Black Casing
	Lid Colour	Black Lid
	Ledge / Hold-down	No Ledge (NL)
	Vent	Centralized venting

36 Months Warranty*

**for PRIVATE passenger vehicle use, subject to terms and conditions*

DIMENSIONAL SPECIFICATIONS	
OVERALL DIMENSIONS	METRIC (mm)
LENGTH	238
WIDTH	129
HEIGHT (bottom to top cover)	205
TOTAL HEIGHT (bottom to top of terminal)	225
NOMINAL WEIGHT	13 kg

TERMINAL DATA	POSITIVE	NEGATIVE
TYPE	JIS	JIS
TERMINAL HEIGHT (mm)	18.5±1.50	18.5±1.50
BOTTOM DIAMETER (mm)	14.7±0.3	13.0±0.3
TAPER	1:9	1:9
POLARITY		

TECHNICAL SPECIFICATIONS	
COLD CRANKING AMPS (CCA)	460 CCA
	Test reference: AS60095.1: 2022 Rated CCA DCH at 18°C for 30 sec
CAPACITY (RC)	90 mins
	Test reference: AS60095.1: 2022 25 Amps DCH at 10.5 V cut-off voltage

AMPERE-HOUR (20-HOUR CAPACITY)	55 AH
	Test reference: AS60095.1: 2022
	Rated AH DCH at 10.5 V cut-off
PLATE DESIGN	Lead-Calcium Alloy Full Frame Plate Design
ELECTROLYTE	36% H2SO4 at 15°C