



Batteries

PRODUCT DETAILS

PRODUCT CODE	XLN1MF	
CHARACTERISTIC	Lead-Acid (Enhanced Flooded Battery)	
GROUP SIZE	N44H	
CASE AND LID	Material : Polypropylene (PP)	
	Handle : 1pc plastic	
	Ledge : EL & FL	
	Venting System : Centralized system with degassing vents on sides	36 Months Warranty*

DIMENSIONAL SPECIFICATIONS

OVERALL DIMENSIONS	METRIC (mm)
LENGTH	207
WIDTH	174
HEIGHT (bottom to top cover)	190
TOTAL HEIGHT (bottom to top of terminal)	190
APPROXIMATE WEIGHT, kg	12.5


TERMINAL DATA	POSITIVE	NEGATIVE
TYPE	SAE	SAE
TERMINAL HEIGHT (mm)	18.5±1.50	18.5±1.50
BOTTOM DIAMETER (mm)	19.5+0/-0.3	19.5+0/-0.3
TAPER	1:9	1:9
POLARITY	C (Positive Left)	

CAPACITY SPECIFICATIONS


COLD CRANKING AMPS (CCA)	450 CCA
	Test reference: AS60095:2022 Rated CCA DCH at 18°C for 30 sec
AMPERE-HOUR AT 20-HOUR CAPACITY	52 Ah
	Test reference: AS60095:2022 Rated AH DCH at 10.5 V cut-off voltage

RESERVE CAPACITY TEST	91 min
	Test reference: AS60095:2022 25Amps DCH at 10.5V cut-off voltage



B13



(STANDARD)



0



*Warranty terms and conditions apply